

P-97 FLAMING/BROWN MICROPIPETTE PULLER P-97 程控水平微电极拉制仪



The **P-97** micropipette puller is the latest generation of the Flaming/Brown type puller for fabrication of micropipettes, patch pipettes and microinjection needles. While retaining many of the features of earlier models, the **P-97** offers improvements in mechanical, electronic and software design. The result is better control of the pulling process and a higher degree of reproducibility. The **P-97** combines a proven mechanical system with a sophisticated, programmable microprocessor controller. This programmable control of the pulling parameters allows the investigator to design application specific pipettes from a wide range of glass compositions and sizes.

A number of other features have been incorporated in the design of the **P-97**. One

of the most apparent is the environmental chamber which houses the area surrounding the heating filament. The environmental chamber is designed to minimize the effect of changing humidity on the reproducibility of pulled pipettes. A 25% increase in power over the previous version allows for the use of larger heating filaments, larger diameter glass and multi-barreled glass. The metal jaws that clamp the heating filament have also been redesigned to minimize heat retention. There are two modes of cooling: time and delay. The delay mode provides extended cooling for large diameter and multi-barreled glass. A spring-loaded clamping mechanism has been added for easier loading of glass. A vacuum fluorescent display has been added that allows easy viewing from any direction.

马普科学仪器有限公司

Tel:020-8767 9617 , 87679631; Fax:020-8767 9635
<http://www.mapusci.com> E-mail:info@mapusci.com

Software improvements on the **P-97** include a display of the total time that the heat is on to assist in program development and troubleshooting. Up to 100 programs can now be written and stored in memory, which makes the **P-97** suitable for multiple users. These programs can now be write-protected, adding security to prevent programs from being changed or altered inadvertently. The display shows the last date and time the program was written or edited. In addition, the air pressure is a programmable parameter.

* Patent No. 4,600,424

FEATURES

> **P-97**

Environmental chamber	Internal memory test
Programmable air pressure	Constant current power supply for filament and pull solenoid
Memory storage for up to 100 programs	Looping pull cycle for fabrication of patch type micropipettes
Write protection and date stamp for each program	Self-contained air supply with filtration system and humidity control
Two symmetrical pipettes with each pull	Consistent and reliable electrodes with tip diameters less than $0.1\mu\text{m}$
Two cooling modes: time and delay	Control over the time and pressure at which the air is delivered
Preprogrammed sample programs for intracellular and patch pipettes. Special programming on request	Optimized velocity sensing circuit for maximized sensitivity and reproducibility
Ramp test to establish program heat settings when a new filament or glass is introduced	Quality control, SEM photograph of a tip pulled with each puller; criterion is tip measurement less than $0.1\mu\text{m}$ and typically is $\sim 0.06\mu\text{m}$
Vacuum fluorescent display	

马普科学仪器有限公司

Tel:020-8767 9617 , 87679631; Fax:020-8767 9635

<http://www.mapusci.com> E-mail:info@mapusci.com

SPECIFICATIONS> **P-97****Dimensions**21in x 14in x 12in
53cm x 36cm x 30cm**Weight**62lbs
29kg**Electrical**115/230 Volts
50/60 Hertz power line**REFERENCES > P-97**

These references describe the Flaming/Brown series of pullers and contain valuable information applicable to the **P-97**.

1. Brown, K.T. and Flaming, D.G. *Neurosciences Journal*: 2:813-827, 1977.
2. Flaming, D.G. and Brown, K.T., *Journal of Neuroscience Methods*: 6:91-102, 1982.
3. Brown, K.T. and Flaming, D.G., *Advanced Micropipette Techniques for Cell Physiology*. John Wiley and Sons. Great Britain, 1986.

马普科学仪器有限公司

Tel:020-8767 9617 , 87679631; Fax:020-8767 9635
<http://www.mapusci.com> E-mail:info@mapusci.com

US PRICES> **P-97**

*International prices are 5% higher.
Prices subject to change without notice.*

P-97 Flaming/Brown type micropipette puller, manual, and Pipette Cookbook

*Each puller comes with an assortment of 4 filaments and a sample box of BF100-50-10 and BF150-86-10 glass. Sutter pre-programs the **P-97** with a 2.5mm box filament unless an alternative filament is requested.*

ACCESSORIES

FPS Fire polishing spacer for P-97 and P-87 pullers

CTS Ceramic tile for scoring glass
(large tips 20-200 microns)

BX10 Pipette storage box* (holds 10)
4 3/4 x 3 5/8 x 3/4 inches

BX20 Pipette storage box* (holds 20)
7 x 3 5/8 x 3/4 inches

** Minimum order of any 2 boxes*



马普科学仪器有限公司

Tel:020-8767 9617 , 87679631; Fax:020-8767 9635
<http://www.mapusci.com> E-mail:info@mapusci.com